



Nordstrom 1200 Valve Sealant

Nordstrom 1200 Valve Sealant is a fluoroalkylether-based lubricant with a PTFE thickener specifically designed to be highly resistant to extremely aggressive chemicals at low carbon dioxide concentrations. It exhibits good resistance to shear and a very broad usable temperature range.

Recommended Temperature Range

BULK	-33° to 400° F (-36° to 204° C)
HT	-22° to 550° F (-30° to 288° C)
LT	-94° to 150° F (-70° to 66° C)

Typical Physical Properties

		<u>Bulk</u>	<u>HT</u>	<u>LT</u>
Color		White	White	White
Density (g/cm ³)		1.89 - 1.93	1.89 - 1.93	1.89 - 1.93
Penetration @ 77° F (25°C),	Unworked	178	178	178
	Worked	192	192	192
Equivalent NLGI Grade		4	4	4
Dropping Point °F		N/A	N/A	N/A
	°C	N/A	N/A	N/A
Flash Point °F		---	---	---
	°C	---	---	---

The information and data presented are based upon laboratory evaluation. However, because of the varied conditions under which this product may be used, the same results as those described here may not be obtained. Samples are available, and each user should independently determine the suitability of this product for their specific purposes.

Date: 6/19/2002