



Nordstrom 167 Valve Sealant

Nordstrom 167 valve sealant is a high temperature lubricating composition consisting of selected hydrocarbon oils thickened with inorganic thickeners. It is recommended for high temperature water, steam, and hot oil/steam combinations. It is not suitable for use with liquid light hydrocarbons, aromatic solvents, and nitrating acids.

Recommended Temperature Range

Bulk 20° to 650°F (-6.7° to 343°C)
Stick 50° to 650°F (10° to 343°C)

Typical Physical Properties

		<u>Bulk</u>	<u>Stick</u>	<u>SS</u>
Color		Tan	Tan	Tan
Density (g/cm ³)		0.82	0.90	0.90
Penetration @ 77° F (25°C),	Unworked	146	83	214
	Worked	157	101	224
Equivalent NLGI Grade		5	6	3
Dropping Point °F		>450	>450	>450
	°C	>232	>232	>232
Flash Point °F		>450	>450	265
	°C	>232	>232	129.5
Fire Point °F		470	470	-----
	°C	243.5	243.5	-----

The information and data presented are based upon laboratory evaluation. However, because of the varied conditions under which this product may be used, the same results as those described here may not be obtained. Samples are available, and each user should independently determine the suitability of this product for their specific purposes.

Date: 6/19/2002