



Nordstrom 234 Valve Sealant and O-Ring Lubricant

Nordstrom 234 valve sealant and o-ring lubricant is a silicone sealing compound with a microsilica thickener. It is recommended for hot air, hot water, steam, high vacuum, acetic acid, acetic anhydride, ethyl alcohol below 250 °F, natural gas compressor discharge, and food and pharmaceutical applications as determined suitable by the user. Nordstrom 234 valve sealant is NSF 61 approved for use in potable water systems and U.S.D.A H-1 approved for food applications.

Recommended Temperature Range

Bulk -40° to 400°F (-40° to 204°C)

Typical Physical Properties

		<u>Bulk</u>
Color		White
Density (g/cm ³)		1.03
Penetration @ 77° F (25°C),	Unworked	214
	Worked	252
Equivalent NLGI Grade		3
Dropping Point °F		>430
	°C	>221
Flash Point °F		450
	°C	232
Fire Point °F		>500
	°C	>260

Packaging: 5.3 oz. Tubes (2 Tubes / Box)
GunPaks (6 / Box for use in 400-D Handgun)
5 QT Can (Net Wt. 10 lbs.)
5 Gal. Pail (Net Wt. 42 lbs.)
55 Gal. Drum

The information and data presented are based upon laboratory evaluation. However, because of the varied conditions under which this product may be used, the same results as those described here may not be obtained. Samples are available, and each user should independently determine the suitability of this product for their specific purposes.

Date: 6/19/2002